

Protective Fencing

To be erected prior to the commencement of all works on site, and retained in place throughout construction.
Specification: To comprise of 2m tall welded mesh panels on rubber or concrete feet. Panels are to be joined together using a minimum of two anti-tamper couplers, installed so that they can only be removed from inside the fence. The panels should be supported on the inner side by stabilizer struts, which should be attached to a base plate and secured with ground pins.
All weather notices should be erected at regular intervals on the weld mesh panels with words such as "Construction exclusion zone - Keep out".

Tree Protection Area
KEEP OUT
Do **not** move this fence

(TOWN & COUNTRY PLANNING ACT 1990)
TREES ENCLOSED BY THIS FENCE ARE PROTECTED BY PLANNING CONDITIONS AND/OR ARE THE SUBJECT OF A TREE PRESERVATION ORDER.
CONTRAVENTION OF A TREE PRESERVATION ORDER MAY LEAD TO CRIMINAL PROSECUTION
ANY INCURSION INTO THE PROTECTED AREA MUST BE WITH THE WRITTEN PERMISSION OF THE LOCAL PLANNING AUTHORITY

ARBTECH
Arbtech Consulting Limited
Unit 3, Well House Barns, Chester Road, Chester, CH4 0DH
01244 661170

Trunk Protection

Protective hoarding:
To be erected prior to the commencement of all works on site, and retained in place throughout construction. To comprise of 2.4m wooden site hoarding constructed upon a timber frame work situated around the outside of the planting pit. Where the timber frame is constructed around the tree trunk a minimum of 4 layers of clean dry hessian is to be wrapped around the trunk to protect the bark.
All weather notices should be erected at regular intervals on the weld mesh panels with words such as "Construction exclusion zone - Keep out".

'No Dig' Surfacing

Replacement hard surfacing to be situated within the RPAs of tree nos. H01, H02, H03 & T04 is to be designed in conjunction with arboricultural advice to ensure that the construction will be situated entirely above the existing soil level and will not require excavation into the RPAs of the tree & the existing hard surfacing sub-base will be retained. Finishing course is to be permeable.

The main site plan illustrates the layout of a property with various trees and their designated protection areas. Trees are labeled with codes: T01, T02, T03, T04, H01, H02, H03, and G01. Each tree has a corresponding Root Protection Area (RPA) outlined in a specific color (green for T01, T03, T04; blue for T02; red for H01, H02, H03; and black for G01). A red dashed line indicates the boundary for Protective Fencing. Blue dashed lines show Trunk Protection for trees T01, T02, and T04. Green dashed lines indicate 'No Dig' surfacing areas for trees H01, H02, H03, and T04. The plan also shows building footprints, parking areas, and landscaping details. A north arrow is located in the top right corner, and a scale bar from 0m to 10m is at the bottom right.

Tree Categories

Trees are categorised in accordance with the cascade chart in Table 1 of the British Standard BS 5837:2012 'Trees in relation to design, demolition and construction - Recommendations'

Category 'U' - Trees in such condition that they cannot realistically be retained as living trees in context of the current land use for longer than 10 years.

Category 'A' - Trees of high quality with an estimated remaining life expectancy of at least 40 years.

Category 'B' - Trees of moderate quality with an estimated remaining life expectancy of at least 20 years.

Category 'C' - Trees of low quality with an estimated remaining life expectancy of at least 10 years, or young trees with a stem diameter below 150mm.

Root Protection Area

In order to avoid damage to the roots or rooting environment of retained trees, the Root Protection Areas (RPAs) should be plotted around each of the category A, B and C trees. This is a minimum area in m² which should be left undisturbed around each retained tree.

The RPA is calculated using the British Standard BS 5837:2012 'Trees in relation to design, demolition and construction - Recommendations.'

The calculated RPA is capped to 707m², which is the equivalent to a circle with a radius of 15m. Where there appears to be restrictions to root growth the root protection area is reshaped to more accurately reflect the likely distribution of the roots.

Arboricultural Impacts Addressed

No.	Species	Proposed structure	Incursion
H01	Various	Hard surfacing replacement	RPA
H02	Various	Hard surfacing replacement	RPA
H03	Various	Hard surfacing replacement	RPA
T04	Ginkgo	Hard surfacing replacement	RPA

Arboricultural Supervision

The arboricultural consultant will be required to attend site to directly supervise all demolition and construction works that have to be undertaken within the root protection areas. This will include:

1. Pre-commencement site meeting.
2. Location of protective measures.
3. Hard surfacing removal & replacement above the RPA of tree T04.
4. Any demolition and or excavations within or adjacent to RPAs, including foundations, hard surfacing or underground services (a non-exhaustive list).

Arboricultural Method Statement

Please refer to Arbtech Consulting Ltd, Tree Schedule and Arboricultural Method Statement, for full details on all surveyed trees and how all aspects of the development maybe implemented without detriment to retained trees.

arbtech

Unit 3, Well House Barns, Chester, CH4 0DH
https://arbtech.co.uk, 01244 661170

Project:

24 Cholmeley Crescent,
Haringey,
London,
N6 5HA

Client:

Lauren Sweet

Drawing:

Tree Protection Plan

Based on:

797 104-105 A

Drawing No:

Arbtech TPP 01

Rev:

Date:

Aug 2023

Scale:

1:50 @ A1

Drawn:

AST

Key:

Tree Nos.:	T1	Tree Canopies:	Trunks:	
RPAs:	Category 'B' trees:	Category 'C' trees:		
Category 'C' groups:	Protective fencing:	Trunk protection:		
'No Dig' Hard surfacing:	Proposed tree planting:			

All dimensions should be checked on site. No dimensions are to be scaled from this drawing. Please notify us of any discrepancies found. Arbtech Consulting Ltd cannot be held responsible for inaccuracies in the base drawing in which this plan is based.
This drawing is designed to reflect the principles of the layout or design only, and relates only to the protection of retained trees.
This drawing is not to be read as a definitive part of the engineering or construction design or method statement. An architect or structural engineer should be contacted over any matters of construction, detailing or specification and for any standards or regulatory requirements relating to proposed structures, hard surfacing or underground services.
This drawing was produced in colour - a monochrome copy should not be relied upon.

© Arbtech Consulting Ltd, 2023