

The images below show the proposed products. Finishes may differ, please refer to the Legend for correct finishes chosen.



L03 LOGIC W L 930 N

L06 OBLIX 40 930 N

L07 KIX S PIN 93010 N

P01 FTL25 F - PROFILE B

P02 SHL 18 - PROFILE 3m ANO

Ground Floor

Scale 1:50

Legend										Lighting fixtures integrated in furniture and/or architecture		
										Floor lighting fixtures		
Ref	Qty	Product Description	Mounting Type	Finish	Light Source	Unit W	Power Supply	Tot W				
L03	4	LOGIC W L 930 N	Wall-Recessed	Anthracite	LED 3000K CR90 9.4W 1380lm 300mA	10.8	integrated	43.2				
L06	7	OBLIX 40 930 N	Floor-Surface mounted	Anthracite	LED 3000K CR90 5.8W 787lm 350mA	6.7	integrated	46.7				
L07	24	KIX S PIN 93010 N	Floor-Surface mounted	Anthracite	LED 3000K 10' CR90 1.4W 178lm 500mA	1.6	remote	38.6				
P01.01	3	FTL25 F - PROFILE B 1451mm	Ceiling-Surface mounted	Black	3000K CR90 3Wlm 480mm 1mA	5.0	remote	15.0				
P01.02	2	FTL25 F - PROFILE B 1151mm	Ceiling-Surface mounted	Black	3000K CR90 3Wlm 480mm 1mA	4.0	remote	7.9				
P01.03	1	FTL25 F - PROFILE B 2981mm	Ceiling-Surface mounted	Black	3000K CR90 3Wlm 480mm 1mA	10.2	remote	10.2				
P01.03	1	FTL25 F - PROFILE B 2981mm	Ceiling-Surface mounted	Black	3000K CR90 3Wlm 480mm 1mA	10.2	remote	10.2				
P01.04	8	FTL25 F - PROFILE B 381mm	Ceiling-Surface mounted	Black	3000K CR90 3Wlm 480mm 1mA	1.2	remote	9.7				
P02.01	1	SHL 18 - PROFILE 3m ANO 350mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	51.8				
P02.02	2	SHL 18 - PROFILE 3m ANO 850mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	103.5				
P02.03	4	SHL 18 - PROFILE 3m ANO 1100mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	207.0				
P02.04	5	SHL 18 - PROFILE 3m ANO 1500mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	258.8				
P02.05	2	SHL 18 - PROFILE 3m ANO 1600mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	103.5				
P02.06	1	SHL 18 - PROFILE 3m ANO 1800mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	51.8				
P02.07	2	SHL 18 - PROFILE 3m ANO 1950mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	103.5				
P02.08	2	SHL 18 - PROFILE 3m ANO 2300mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	103.5				
P02.09	4	SHL 18 - PROFILE 3m ANO 3100mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	207.0				
P02.10	2	SHL 18 - PROFILE 3m ANO 4350mm	Railing-Surface mounted	Alu Anodized	3000K CR90 45Wlm 3200mm 1mA	51.8	remote	103.5				
								Total Wattage	1475.3			

*FE (Railing edge) to dim this lighting fixture you need a remote fading edge dimmer (not provided by Deltalight)

NOTES:

- Lxx: Air/Ventilation System - Lxx: Lighting fixture - Mxx: Magnetic Profile - Pxx: Profile - Txx: Track
- Architectural layouts always have priority on lighting layouts to look for information about the architectural project
- The final quantity of lighting fixtures and their technical features have to be verified by the general contractor prior to order the products. This is to be sure that there is a correspondence among the lighting layout, the electrical layout and the architectural layout.
- We recommend to place all the remote power supplies in a technical space to reduce the timing of the installation, maintenance and programming.
- We recommend to follow the installation manuals of the lighting fixtures to proceed to their installation.

Project Name
Tottenham Externals

Architect/Designer
F3 Architects LLP

City (Country)
London

Title
Tottenham Externals

Layout
Exterior Lighting

N° Drawing
1/1

Scale
1:50 / A2 / mm

Date / Revision
14.07.2025 / 02

File Name
L-202505110 Tottenham Externals_R02.dwg

DELTA LIGHT
Delta Light UK
86-88 Great Suffolk Street
London SE1 1BBE
T +44 (0)20 757 7087
LAD-uk@deltaight.co.uk
www.deltaight.co.uk

Project Code
OPP-202505110

Lighting Advisor
Anthony McCreddie@deltaight.co.uk

Project Consultant
Anthony McCreddie@deltaight.co.uk