


ELECTRICAL SERVICES SYMBOL LEGEND:



CU	CONSUMER UNIT
DB	DOOR BELL
DW	DISHWASHER
EH	EXTRACT COOKER HOOD
FF	FRIDGE FREEZER
G	4 PLATE GRID SWITCH
H/L	HIGH LEVEL
HOB	HOB COOKER
L/L	LOW LEVEL
M/L	MID LEVEL
WP	WEATHER PROOF
WM	WASHING MACHINE
S	SHAVER SOCKET
TR	TOWEL RAIL (ELECTRIC)
UFHM	UNDERFLOOR HEATING MANIFOLD



LIGHTING NOTES:

- * DRAWING TO BE READ IN CONJUNCTION WITH CLIENTS ER's & CONTRACT DOCUMENTS
- * SETTING OUT TO BE CO-ORDINATED ON SITE WITH STUD POSITIONS
- * WHERE OUTLETS ARE ADJACENT ALLOW FOR A 40mm GAP BETWEEN
- * ALL EQUIPMENT TO BE INSTALLED IN LINE WITH MANUFACTURERS RECOMMENDATIONS
- * DRAWING TO BE READ IN CONJUNCTION WITH LUMINAIRE SCHEDULE

- * DRAWING TO BE READ IN CONJUNCTION WITH CLIENTS ER'S & CONTRACT DOCUMENTS
- * INSTALLATION TO BE CO-ORDINATED WITH MECHANICAL DRAWINGS
- * SETTING OUT TO BE CO-ORDINATED ON SITE WITH STUDIOS POSITIONS
- * WHERE OUTLETS ARE ADJACENT ALLOW FOR A 40mm GAP BETWEEN
- * ALL EQUIPMENT TO BE INSTALLED IN LINE WITH MANUFACTURERS RECOMMENDATIONS
- * SETTING OUT IN LINE WITH ARCHITECT FURNITURE LAYOUTS
- * NO BACK TO BACK SOCKETS OR ACCESSORIES
- * THE CONTRACTOR SHALL NOTE THE FOLLOWING:
 - DISTRIBUTION BOARD - 1350mm AFFL TO SWITCHES
 - SOCKETS & SWITCHES - 450-1200mm AFFL
 - SOCKET OUTLETS TO BE AT LEAST 300mm AWAY FROM ANY INTERNAL CORNER
 - ALL TV POINTS, THERMISTATS ETC.
- * TO ALSO BE IN COMPLIANCE WITH PART M
- * WITHIN KITCHENS, ALL ELECTRICAL ACCESSORIES ABOVE WORKTOP LEVEL ARE TO BE INSTALLED 300mm(MINIMUM) CLEAR FROM SINK/DRAINER & 150mm (MINIMUM) CLEAR OF HOB

APARTMENT SCHEDULE	
DOOR NO.	DWELLING TYPE
UNIT 32	TYPE K DUPLEX

P05	27.01.25	APPROVAL ISSUE	EA	EA	NT
P04	05.09.24	APPROVAL ISSUE	JJ	SH	CD
P03	02.05.24	PRELIMINARY ISSUE	JJ	DS	CD
P02	24.04.24	PRELIMINARY ISSUE	JJ	DS	CD
P01	05.04.24	PRELIMINARY ISSUE	JJ	SH	CD
Rev.	Date:	Description:	Eng:	Drn:	App:



BRUNEL WALK

TYPE K DUPLEX UNIT 32 ELECTRICAL LAYOUT

Drawing Status:	Revision:
STAGE 4 - APPROVAL	P05

0053-KCL-00-ZZ-D-E-2211

