






SC 50kg High Explosive Bomb		
Bomb Weight	40-54kg (88-119lb)	
Explosive Weight	25kg (55lb)	
Fuze Type	Impact fuze/electro-mechanical time delay fuze	
Bomb Dimensions	1,090 x 280mm (42.9 x 11.0in)	
Body Diameter	200mm (7.87in)	
Use	Against lightly damageable materials, hangars, railway rolling stock, ammunition depots, light bridges and buildings up to three stories.	
Remarks	The smallest and most common conventional German bomb. Nearly 70% of bombs dropped on the UK were 50kg.	

SC 250kg High Explosive Bomb		
Bomb Weight	245-256kg (540-564lb)	
Explosive Weight	125-130kg (276-287lb)	
Fuze Type	Electrical impact/mechanical time delay fuze	
Bomb Dimensions	1640 x 512mm (64.57 x 20.16in)	
Body Diameter	368mm (14.5in)	
Use	Against railway installations, embankments, flyovers, underpasses, large buildings and below-ground installations.	
Remarks	It could be carried by almost all German bomber aircraft and was used to notable effect by the Junkers Ju-87 Stuka (Sturzkampfflugzeug, or dive-bomber).	

SC 500kg High Explosive Bomb		
Bomb Weight	480-520kg (1,058-1,146lb)	
Explosive Weight	250-260kg (551-573lb)	
Fuze Type	Electrical impact/mechanical time delay fuze	
Bomb Dimensions	1957 x 640mm (77 x 25.2in)	
Body Diameter	470mm (18.5in)	
Use	Against fixed airfield installations, hangars, assembly halls, flyovers, underpasses, high-rise buildings and below-ground installations.	
Remarks	40/60 or 50/50 Amatol TNT, Triale. Bombs recovered with Triale filling have cylindrical paper-wrapped pellets, 1-15/16in. in length and diameter.	

SD2 Anti-Personnel 'Butterfly Bomb'


Bomb Weight	Approx. 2kg (4.41lb)
Explosive Weight	Approx. 7.5oz (225 grams) of Amatol surrounded by a layer of bituminous composition.
Fuze Type	41 fuze (time) , 67 fuze (clockwork time delay) or 70 fuze (anti-handling device)
Body Diameter	3in (7.62 cm) diameter, 3.1in (7.874) long
Use	Designed as an anti-personnel/fragmentation weapon. They were delivered by air, being dropped in containers of 23-144 sub-munitions that opened at a predetermined height, thus scattering the bombs.
Remarks	Quite rare. First used against Ipswich in 1940, but were also dropped on Kingston upon Hull, Grimsby and Cleethorpes in June 1943, amongst various other targets in UK. As the bombs fell the outer case flicked open via springs which caused four light metal drogues with a protruding 5 inch steel cable to deploy in the form of a parachute & wind vane, which armed the device as it span.





Parachute Mine (Luftmine B / LMB)


Bomb Weight	Approx. 990kg (2176lb)
Explosive Weight	Approx. 705kg (1,554lb)
Fuze Type	Impact/time delay/hydrostatic pressure fuze
Dimensions	2.64m x 0.64m (3.04m with parachute housing)
Use	Against civilian, military and industrial targets. Used as blast bombs and designed to detonate above ground level to maximise damage to a wider area.
Remarks	Deployed a parachute when dropped in order to control its descent. Had the potential to cause extensive damage within a 100m radius.





SC 1000kg High Explosive Bomb

Bomb Weight	Approx. 993-1027kg (2,189-2,264lb)
Explosive Weight	Approx. 530-620kg (1168-1367lb)
Fuze Type	Electrical impact/mechanical time delay fuze.
Filling	Mixture of 40% amatol and 60% TNT, but when used as an anti-shipping bomb it was filled with Trialen 105, a mixture of 15% RDX, 70% TNT and 15% aluminium powder.
Bomb Dimensions	2800 x 654mm (110 x 25.8in)
Body Diameter	654mm (18.5in)
Use	SC-type bombs were General Purpose Bombs used primarily for general demolition work. Constructed of parallel walls with comparatively heavy noses, they are usually of three-piece welded construction.







Unit 3, Maple Park,
Essex Road, Hoddesdon,
Hertfordshire. EN11 0EX
Email: info@1stlinedefence.co.uk
Tel: +44 (0)1992 245 020

Client: YMCA London City and North


Project: YLCAN – Crouch End


Ref: DA22141-00


Source: Various sources


1kg Incendiary Bomb	
Bomb Weight	Approx. 1.0 - 1.3kg (2.2 and 2.9lb)
Explosive Weight	Approx. 680g (1.5lb) Thermit 8-15gm Explosive Nitropenta
Fuze Type	Impact fuze
Bomb Dimensions	350 x 50mm (13.8 x 1.97in)
Body Diameter	50mm (1.97in)
Use	As incendiary – dropped in clusters on towns and industrial complexes.
Remarks	Magnesium alloy case. Sometimes fitted with high explosive charge. The body is a cylindrical alloy casting threaded internally at the nose to receive the fuze holder and fuze.

C50 A Incendiary Bomb		
Bomb Weight	Approx. 41kg (90.4lb)	
Explosive Weight	Approx. 0.03kg (0.066lb)	
Incendiary Filling	12kg (25.5lb) liquid filling with phosphor igniters in glass phials. Benzine 85%; Phosphorus 4%; Pure Rubber 10%	
Fuze Type	Electrical impact fuze	
Bomb Dimensions	1,100 x 280mm (43.2 x 8in)	
Use	Against any targets where an incendiary effect is required.	
Remarks	Early fill was a phosphorous/carbon disulphide incendiary mixture.	

Flam C-250 Oil Bomb		
Bomb Weight	480-520kg (1,058-1,146lb)	
Explosive Weight	250-260kg (551-573lb)	
Fuze Type	Electrical impact/mechanical time delay fuze	
Bomb Dimensions	1957 x 640mm (77 x 25.2in)	
Body Diameter	470mm (18.5in)	
Use	Against fixed airfield installations, hangars, assembly halls, flyovers, underpasses, high-rise buildings and below-ground installations.	
Remarks	40/60 or 50/50 Amatol TNT, Trialene. Bombs recovered with Trialen filling have cylindrical paper-wrapped pellets, 1-15/16in. in length and diameter.	

3.7 Inch QF Anti-Aircraft Projectile			 
Projectile Weight	28lb (12.6 kg)		
Explosive Weight	2.52lbs		
Fuze Type	Mechanical Time Fuze		
Dimensions	3.7in x 14.7in (94mm x 360mm)		
Rate of Fire	10 to 20 rounds per minute		
Use	The 3.7in AA Mk 1-3 were the standard Heavy Anti-Aircraft guns of the British Army and were commonly used on the Home Front.		
Ceiling	30,000ft to 59,000ft		

40mm Bofors Projectile				
Projectile Weight	1.96lb (0.86kg)			
Explosive Weight	300g (0.6lb)			
Fuze Type	Impact Fuze			
Rate of Fire	120 rounds per minute			
Projectile Dimensions	40 x 180mm			
Ceiling	23,000ft (7000m)			
Remarks	Light quick fire high explosive anti-aircraft projectile. Each projectile fitted with small tracer element. If no target hit, shell would explode when tracer burnt out. Designed to engage aircraft flying below 2,000ft.			

3in Unrotated Projectile (UP) Anti-Aircraft Rocket ("Z" Battery)			
HE Projectile Weight	3.4kg (7.6lb)		
Explosive Weight	0.96kg (2.13lb)		
Filling	High Explosive – TNT. Fitted with aerial burst fuzing		
Dimensions of projectile	236 x 83mm (9.29 x 3.25in)		
Remarks	As a short range rocket-firing anti-aircraft weapon developed for the Royal Navy. It was used extensively by British ships during the early days of World War II. The UP was also used in ground-based single and 128-round launchers known as Z Batteries. Shell consists of a steel cylinder reduced in diameter at the base and threaded externally to screw into the shell ring of the rocket motor.		

1st Line Defence

Unit 3, Maple Park
Essex Road, Hoddesdon
Hertfordshire EN11 0EX

Call +44 (0) 1992 245 020

Email info@1stlinedefence.co.uk

Web www.1stlinedefence.co.uk

