

Hornsey Town Hall

Blocks A, B, Mews and Annexe Schedule of Luminaires

Prepared for Ardmore

10687-LUMSCHD-0001

Revision C3

07 December 2022



WHITECODE
CONSULTING



10687 Hornsey Town Hall**Blocks A,B, Mews and Annexe Schedule of Luminaires****10687-LUMSCHD-000(1)****WHITECODE**
CONSULTING

Ref	Description	Locations	Manufacturer and Catalogue Number	Lamp	Image
B1	IP65 LED surface fixture with polycarbonate construction and anti-glare diffuser	HA apartments	Orlight ORL-X14	14W 4000K	
D1a	IP20-rated circular ceiling-recessed LED downlight with white powder coated, satin matt finish, colour.	Apartments Communal – outside lift	TRILUX SNCPOINT 905	9W LED 700 lm Fixed output 3000K	
D1b	5W low energy adjustable, dimmable downlight as Orlight ORL1019MAXIAW.	Penthouse	TRILUX SNCPOINT 905	9W LED 700 lm DALI 3000K	
D2	IP20-rated circular ceiling-recessed LED downlight with white powder coated, satin matt finish, colour. Optics – Flood 60° 'E' Denotes integral 3hr emergency battery pack.	Communal Areas	IBL Cone 80 WW2246.131B WW2246.131B E3D (emergency)	1 x 8.6W LED 911 lm DALI 3000K	
D3a	IP54-rated circular ceiling-recessed LED downlight with white powder coated, satin matt finish, colour.	Apartments (Bathrooms)	TRILUX SNCPOINT 905	9W LED 700 lm Fixed output 3000K	
D3b	IP54-rated circular ceiling-recessed LED downlight with white powder coated, satin matt finish, colour.	Penthouse (Bathrooms)	TRILUX SNCPOINT 905	9W LED 700 lm DALI 3000K	

10687 Hornsey Town Hall**Blocks A,B, Mews and Annexe Schedule of Luminaires****10687-LUMSCHD-000(1)****WHITECODE**
CONSULTING

Ref	Description	Locations	Manufacturer and Catalogue Number	Lamp	Image
D4	IP-54 circular ceiling outdoor downlight with high quality aluminium.	Apartments External Balcony	LUCIDE TUBIX	60W 4000K	
D5	Ceiling recessed plaster in adjustable LED downlight with square reflector installed using plaster in kit for trimmed installation. IP40. Wide Flood 46 degree beam angle	Communal areas	Kreon: KR907733 -9030-FL	2W LED 3000K	
D6	Stirrup mounted adjustable LED projector mounted within ceiling screen structure. Mounting detail to follow. Remote DALI driver	Block B entrance	Superlight Nano 1 / 8 817 046 048 VAR	3W LED 3000K	
E1	Recessed non-maintained emergency fitting. With escape route optic.	Communal areas	ETAP: K9 Mini Recessed escape route optic K9R013/3NS211	3W 4000K	
F8	IP20-rated batten luminaire, suitable for surface-mounting to wall, complete with aluminium housing and frosted PC optical cover. Note: Emergency use lights to be with DALI-compatible driver [separate] see note 4. 'E' Denotes integral 3hr emergency battery pack.	Apartment cupboards and risers	Osram LUMCombi	10W LED 4000K	

10687 Hornsey Town Hall**Blocks A,B, Mews and Annexe Schedule of Luminaires****10687-LUMSCHD-000(1)****WHITECODE**
CONSULTING

Ref	Description	Locations	Manufacturer and Catalogue Number	Lamp	Image
L1	Surface mounted anti-corrosive luminaire c/w integral 3hr emergency, non-dimmable. IP65. 'E' Denotes integral 3hr emergency battery pack	Car Park	WHITECROFT ACL Industry (ACH34K)	27W LED 3865 lm Fixed output 4000K	
L2	Surface mounted anti-corrosive luminaire c/w integral 3hr emergency, non-dimmable. IP65. 'E' Denotes integral 3hr emergency battery pack	Bin stores, cycle stores & corridors	WHITECROFT ACL Industry (ACH34K)	27W LED 3865 lm Fixed output 4000K	
L3	Single surface mounted luminaire made of glass fibre reinforced polyester. Diffuser made of polycarbonate with stainless steel c/ w integral 3hr emergency, non-dimmable. IP67. 'E' Denotes integral 3hr emergency battery pack	Plantrooms	FAGERHULT Kaptur Lite (34335)	45W LED 5719 lm Fixed output 4000K	
L4B	IP44 Rated LED Linear light with Aluminium extrusion profile. Complete with dimmable compatible control gear.	Penthouse Apartments Bathroom	Orlight REFRACT2	12W/m 787 lm DALI 3000K	
L5A	IP65 rated LED Linear light with recessed linear profile and end cup (white finish). Complete with dimmable DALI compatible control gear.	Apartment kitchens, living areas, bedrooms	Orlight ORLTE6012	4.8W/m 335 lm Fixed Output 3000K	

10687 Hornsey Town Hall**Blocks A,B, Mews and Annexe Schedule of Luminaires****10687-LUMSCHD-000(1)****WHITECODE**
CONSULTING

Ref	Description	Locations	Manufacturer and Catalogue Number	Lamp	Image
L5B	IP65 rated LED Linear light with recessed linear profile and end cup (white finish). Complete with dimmable DALI compatible control gear.	Penthouse apartment kitchens, living areas, bedrooms	Orlight ORLTE6012	4.8W/m 335 lm DALI 3000K	
L6	Surface-mounted LED luminaire with polycarbonate diffuser and dimmable DALI-compatible high frequency ballast. 'E' Denotes integral 3hr emergency battery pack	Communal area stairwells	Whitecroft Stiletto LED STHLED54KEM	47W LED 5300 lm DALI 4000K	
L7	Surface-mounted LED luminaire with powder polyester finish and dimmable DALI-compatible high frequency ballast. 'E' Denotes integral 3hr emergency battery pack	Roof	Designplan Square One LED	56W LED 2821 lm DALI 4000K	
L8	Bathroom wall light	Apartment bathrooms	Bespoke wall light Frandsen Project	TBC	

10687 Hornsey Town Hall

Blocks A,B, Mews and Annexe Schedule of Luminaires

10687-LUMSCHD-000(1)



WHITECODE
CONSULTING

Ref	Description	Locations	Manufacturer and Catalogue Number	Lamp	Image
	Illuminated Exit Sign Surface plate with floating glass (Illuminated).	Corridor and escape routes	Phillip Payne (2-NI)	4W (LED) DALI	
P1	Wall mounted suspended pendant luminaire with spherical glass cover by others. Fitting design to be reviewed by PTL prior to manufacture	Block B Ground floor	By others	By others	
P6	Safety pendant lamp holder, ceiling mounted, lamp holder, 150mm drop	HA apartments	Deta Ltd ref: S105/6T2 or approved equivalent	9 Watt 3000K TC-D compact fluorescent lamp, B22 bayonet cap	

Contact details:

Whitecode Consulting Ltd
26-27 The Hill
Northfleet
Gravesend
Kent
DA11 9EU

t: 01322 289977

e: design@whitecode.co.uk



WHITECODE
CONSULTING