

HL/BK4LED600



Code Specification


ASD Lighting Half Lantern, Black, Premium Opal, IP44, 4000K. 118mm Depth, 394mm Height, 182mm Width, Body: Vandal resistant polycarbonate self-extinguishing fire properties in black / white / titanium / other colours on request, Window: Vandal resistant polycarbonate.
Applications not limited to: Residential & Domestic, Social Housing.
UKCA & CE, BS EN 60598, Class I.

Technical Information

Colour	Black
Diffuser	Premium Opal
CCT	4000 K
System Power	7.4 W
Delivered Lumens	283.3 lm
Efficacy	38 lm/W
Weight	1 KG

Dimensions

Depth	118mm
Height	394mm
Width	182mm



HL/BK4LED600



Range Information

A traditional wall mounted Half Lantern ideal for doorways to optimise illumination for entrance areas.

Range Specification

Wall mount
Simple installation
Shatter-proof polycarbonate detector
PIR range of 6 metres
110° angle of detection
Photocell: dusk to dawn sensor
5 Year LED guarantee
Photocell option external use only

Range Options

PIR / Photocell options available
HI-LO PIR (luminaire at 10% during periods of inactivity, 100% light output when HI-LO PIR detects movement)
Fluorescent options available

