

**Northumberland Terrace
(Phase 3)**

798 – 808 High Road

Tottenham

London

Drainage Strategy Report

Job Number: 19068

Revision: P04

Date: 12th March 2020

Table of Contents

1. Introduction..... 3

2. Site Description..... 3

 2.1. Site Location 3

 2.2. Existing Development..... 3

 2.3. Proposed Development..... 3

3. Planning Policy 3

 3.1. National Planning Policy Framework (NPPF) – February 2019..... 3

 3.2. Emerging Draft New London Plan – March 2020 4

 3.3. Haringey Local Plan – February 2013 4

 3.4. Haringey Development Management DPD – July 2017 4

 3.5. Mayor of London – Sustainable Design and Construction (SPG) – April 2014..... 5

4. Existing Drainage..... 5

 4.1. Existing Private Drainage 5

 4.2. Existing Public Drainage 5

5. Drainage Hierarchy 6

6. Proposed Surface Water Drainage Strategy..... 8

 6.1. Impermeable and Permeable Areas..... 8

 6.2. Peak Rate of Runoff..... 8

 6.3. Volume of Runoff..... 8

 6.4. Pre-development Runoff Rates 8

 6.5. Proposed Limiting Discharge Rate 9

 6.6. Attenuation Storage..... 9

 6.7. Maintenance..... 9

7. Foul Water Drainage 9

 7.1. Existing Foul Flows 9

 7.2. Proposed Foul Flows..... 9

 7.3. Consultation 9

8. Conclusion 10

Appendix A – Site Location Plan

Appendix B – Existing Topographic Survey.....

Appendix C – Preliminary Site Layouts.....

Appendix D – Thames Water Asset Map

Appendix E – Ground Investigation.....

Appendix F – Greenfield Runoff Rates.....

Appendix G – Micro Drainage Calculation Sheets

Appendix H – SuDS Proforma.....

Appendix I – Preliminary Site Drainage Layout.....

Document Control

Remarks		Drainage Strategy Report						Date
Rev	P01	Prepared	NG	Checked	NG	Approved	KL	17/10/19
Rev	P02	Prepared	NL	Checked	NG	Approved	KL	22/11/19
Rev	P03	Prepared	NG	Checked	NG	Approved	KL	24/02/20
Rev	P04	Prepared	NG	Checked	NG	Approved	KL	12/03/20

1. Introduction

Lyons O'Neill has been instructed by F3 Architects to prepare a Drainage Strategy Report to support an application for planning and listed building consent application for a major development in North London referred to as Northumberland Terrace.

2. Site Description

2.1. Site Location

The site is located at 798 - 808 High Road (and land to the rear), North London. The site has an area is 0.3765 ha (3,765 m²) and is located at the National Grid reference TQ3392391438 and E533923, N191438. Figure 1 shows the site location and redline planning boundary for the site. A copy of the site plan has been enclosed as Appendix A of this report.




Figure 1 – Site Location

2.2. Existing Development

The land that is being proposed for redevelopment is to the rear of properties 798 – 814 High Road in Tottenham with some being Grade II Listed. The existing site comprises of existing buildings, hard standing and some soft permeable areas. A copy of the existing topographic survey of the site has been enclosed as Appendix B of this report.

2.3. Proposed Development

Proposals in a full planning application for the erection of a four storey building with flexible A1/A2/A3/B1/D1/D2 use; external alterations to 798-808 High Road; change of use of 798-808 High Road to a flexible A1/A2/A3/B1/D1/D2 use; demolition of rear extensions to Nos. 798, 800-802, 804-806, 808 and 814 High Road; erection of new rear extensions to Nos. 798, 800-802, 804-806 and 808 High Road; hard and soft landscaping works; and associated works.

Proposals include listed building consent for internal and external alterations to 798-808 High Road, including the demolition of rear extensions Nos. 798, 800-802, 804-806 and 808 High Road; erection of new rear extensions to Nos. 798, 800-802, 804-806 and 808 High Road; and associated works.

A copy of the proposed site plans are enclosed as Appendix C of this report.

3. Planning Policy

This report has been prepared in line with national, regional and local planning policy. The following strategic documents have been used as guidance to prepare this report:

3.1. National Planning Policy Framework (NPPF) – February 2019

Major developments should incorporate sustainable drainage systems unless there is clear evidence that this would be inappropriate (paragraph 165).

The systems used should:

- a) take account of advice from the lead local flood authority;*
- b) have appropriate proposed minimum operational standards;*
- c) have maintenance arrangements in place to ensure an acceptable standard of operation for the lifetime of the development; and*
- d) where possible, provide multifunctional benefits.*

3.2. Emerging Draft New London Plan – Intend to Publish, December 2019

The new London Plan carries considerable weight therefore the drainage design will adhere to the new *Policy SI13 – Sustainable Drainage*.

Policy SI13 – Sustainable Drainage

- A. Lead Local Flood Authorities should identify – through their Local Flood Risk Management Strategies and Surface Water Management Plans – areas where there are particular surface water management issues and aim to reduce these risks.
- B. Development proposals should aim to achieve greenfield run-off rates and ensure that surface water run-off is managed as close to its source as possible in line with the following drainage hierarchy:
1. rainwater harvesting (including a combination of green and blue roofs)
 2. infiltration techniques and green roofs
 3. rainwater attenuation in open water features for gradual release
 4. rainwater discharge direct to a watercourse (unless not appropriate)
 5. rainwater attenuation above ground (including blue roofs)
 6. rainwater attenuation below ground
 7. rainwater discharge to a surface water sewer or drain
 8. rainwater discharge to a combined sewer
- C. Development proposals for impermeable paving should be refused where appropriate, including on small surfaces such as front gardens and driveways.
- D. Drainage should be designed and implemented in ways that address issues of water use efficiency, river water quality, biodiversity, amenity and recreation.

3.3. Haringey Local Plan – February 2013

SP5: Water Management and Flooding

The Council will require all development in Haringey to be water efficient during construction and operation and to reduce all forms of flood risk. All development shall:

- Improve the water environment, water quality and drainage systems;
- Minimise water use and illustrate how development would contribute to general and flash flooding;
- All development in these areas will take account of flood risk vulnerability classification as set out in paragraph 100 of the NPPF and will apply the NPPF Sequential Test and Exception Test;
- Implement measures to prevent (or mitigate as last resort) local surface water and downstream flooding;

- Implement Sustainable Drainage Systems from strategic to individual site level to improve water attenuation, quality and amenity;
- Restore and enhance the Blue Ribbon Network including Pymmes Brook, Moselle Brook, the River Lee and its tributaries, deculverting wherever feasible, to improve water quality and amenity of these waterways and to help reduce flood risk (in line with London River Action Plan); and
- Require higher resilience and levels of flood protection for critical infrastructure to ensure the protection of essential services such as water and power.

In order to facilitate this, the Council:

- Has carried out a joint SFRA (Strategic Flood Risk Assessment) Stage 1 for the whole borough;
- Has carried out a Sequential Test for the Areas of Development (Growth Areas and Areas of Change);
- Has carrying out, in association with other north London boroughs in the Drain London subregion, a Surface Water Management Plan to identify issues with drainage networks and the effects of new development.

3.4. Haringey Development Management DPD – July 2017

DM25 – Sustainable Drainage Systems

A. All proposals for new development must seek to manage surface water as close to its source as possible in line with the London Plan drainage hierarchy.

B. The Council will require Sustainable Drainage Systems (SuDS) to be sensitively incorporated into new development by way of site layout and design, having regard to the following requirements:

- All major development proposals will be required to reduce surface water flows to a greenfield run-off rate for a 1 in 100 year critical storm event;
- All minor development proposals should aim to achieve a greenfield run-off rate and, at a minimum, achieve a 50 per cent reduction on existing site run-off rates;
All other development should seek to achieve a greenfield run-off rate and include at least one 'at source' SuDS measure resulting in a net improvement in water quantity or quality discharging to a sewer; and

- For all development where a greenfield runoff rate cannot be achieved justification must be provided to demonstrate that the run-off rate has been reduced as much as possible. C

C. Where Sustainable Drainage Systems are implemented they will be expected to:

- Meet the requirements set out in the Council's relevant local standards and guidance, or national standards where agreed;
- Incorporate measures identified in the Surface Water Management Plan;
- Be designed to maximise biodiversity and local amenity benefits, and where appropriate, ensure that SuDS techniques provide for clean and safe water at the surface;
- Improve water quality; and
- Function effectively over the lifespan of the development.

D. Where SuDS cannot be implemented due to site constraints (such as land contamination or space limitations) robust justification must be provided along with proposed alternative sustainable approaches to surface water management.

3.5. Mayor of London – Sustainable Design and Construction (SPG) – April 2014

This document advises that if greenfield runoff rates are not proposed, developers will be expected to demonstrate how all opportunities to minimise final site run-off have been taken.

4. Existing Drainage

4.1. Existing Private Drainage

No CCTV drainage survey has been undertaken at this stage however a utilities drawing has been used to best piece together how the existing drainage network is functioning. A CCTV drainage survey will be required in due course to understand the existing site drainage in more detail.

4.2. Existing Public Drainage

The Thames Water asset map shows a 610mm $\varnothing$ public surface water sewer and 305 mm $\varnothing$ public foul water sewer in High Street and 305mm $\varnothing$ public surface water sewer in Northumberland Park Road. A copy of the Thames Water asset map is included as Appendix D of this report. Figure 2 shows a screenshot of the asset map infrastructure in close proximity to the site.




Figure 2 – Thames Water Asset Plan

5. Drainage Hierarchy

New Policy SI13 (Sustainable Drainage) of the emerging 'draft' London Plan states that a development should utilise sustainable urban drainage systems (SuDS) unless there are practical reasons for not doing so, and should aim to achieve Greenfield run-off rates and ensure that surface water run-off is managed as close to its source as possible in line with the following drainage hierarchy:

Development proposals should aim to achieve greenfield run-off rates and ensure that surface water run-off is managed as close to its source as possible in line with the following drainage hierarchy:

1. rainwater harvesting (including a combination of green and blue roofs)
2. infiltration techniques and green roofs
3. rainwater attenuation in open water features for gradual release
4. rainwater discharge direct to a watercourse (unless not appropriate)
5. rainwater attenuation above ground (including blue roofs)
6. rainwater attenuation below ground
7. rainwater discharge to a surface water sewer or drain
8. rainwater discharge to a combined sewer

Drainage should be designed and implemented in ways that deliver other policy objective of this Plan, including water use efficiency and quality, biodiversity, amenity and recreation.

Table 1 – Feasibility of SuDS Components

Feasibility of SuDS Components	
Infiltrating SuDS	No
Permeable Pavements	No
Green Roofs	No
Rainwater Harvesting	No
Swales	No
Rills and Channels	No
Bio-retention Systems	No
Retention Ponds and Wetlands	No
Wetlands	No
Geo-cellular Systems	Yes
Proprietary Treatment Systems	No
Filter Drains and Filter Strips	No

Store rainwater for later use



Rainwater harvesting and green/brown roofs are often the preferred SuDS as they intercept water at high level and provide other sustainability benefits such as reducing the water demand of the building and increasing biodiversity.


The feasibility of rainwater harvesting will depend on the water reuse demands for the building which will be determined in due course however the design and capacity of attenuation cannot be included in the below ground drainage calculations.

The key benefits of rainwater harvesting are easy to maintain, reducing water bills, reduces demand on groundwater, reduces flooding and soil erosion and can be used for non-drinking purposes.



Green roofs slow the runoff rates from the site however the SuDS manual states that *"the hydraulic performance of green/brown roofs during extreme events tends to be fairly similar to standard roofs"*. Therefore green roofs provide sustainability benefits however they cannot be included in the below ground drainage calculations. Although rainwater harvesting and green roofs are feasible they will not be used within the proposals for this development.

Use infiltration techniques



A site assessment report was produced by Southern Testing in January 2017. Borehole BH09/01 has indicated that Kempton Park Gravels are present at a depth of 1.5 m to 5.4 m below ground level (bgl). Groundwater was also encountered during the investigation initially at 3.9 m bgl rising to 3.3m bgl (8.78 m AOD) and a second strike at 19.6 m bgl rising to 17.3 m bgl. A desk study report on contamination was produced by Southern Testing in July 2016. In summary a number of potential contamination impacts were identified from on-site and off-site sources. Therefore

although the Kempton Park Gravel is a suitable infiltration media the ground conditions are not suitable for disposal of surface water from the site (refer to Appendix E).

Attenuate rainwater in ponds or open water features for gradual release

This part of London is highly urbanised with no ponds or open water features in close proximity to the site. Therefore this method of surface water disposal is not suitable.



Pond / Basin

Attenuate rainwater by storing in tanks or sealed water features for gradual release


Proposals are to use a surface water attenuation tank to store surface water and then release at a restricted discharge rate to the sewer. Therefore attenuating rainwater is a viable option.



Underground
storage

Discharge rainwater direct to a watercourse

There is no watercourse in close proximity to the site therefore, this method of surface water disposal is not suitable.




Discharge rainwater to a surface water sewer/drain

There are no surface water sewers in close proximity to the site.



Discharge rainwater to the combined sewer

Proposals are to construct new connection(s) from the site to the public sewer for both foul and surface water.



6. Proposed Surface Water Drainage Strategy

6.1. Impermeable and Permeable Areas

The existing site has an area of 3,765 m² (100%) of which 3,765m² (100%) is impermeable surfaces that positively drain to the existing network.

The proposed site has an area of 3,765 m² (100%) of which 3,515m² (93%) will be impermeable surfaces that positively drain to the proposed network.

6.2. Peak Rate of Runoff

At this stage, the proposed surface water drainage will connect to the 300 mm diameter sewer located in Northumberland Road where approval will be required. The asset map provided by Thames Water demonstrates that levels will allow a gravity connection to the public sewer.

In accordance with the Haringey Development DPD Policy DM25, developments should ensure that there is no increase in flood elsewhere, and should seek to achieve Greenfield (GF) rates of runoff. There are two approaches for setting the maximum allowable GF discharge rates as detailed in Figure 2 which depend on whether the volume of runoff can be managed.




Figure 2 – Two approaches for managing flows & volumes from a development site

As IoH124 and FSR are considered outdated methods for calculating runoff and rainfall, FEH data has been used which are more up to date and was the preferred method for estimating rainfall and runoff. The following table provides an outline to the anticipated runoff rates for

Haringey based on a clay soil using FEH methodology as per the SuDS Design Requirements for LLFA Technical Assessment Document. A copy of the greenfield runoff rates are enclosed as Appendix F.

Table 2 – Runoff Rates

Return Period	Greenfield Runoff Rates for Site (l/sec)	PDL Sites – 3 Times Greenfield Runoff (l/sec)
1 in 1 year	1.5	4.4
1 in 2 year (Qbar)	1.8	5.4
1 in 30 year	4.2	12.6
1 in 100 year	5.8	17.4

6.3. Volume of Runoff

Attenuation can be provided in the form of geo-cellular crates wrapped in an impermeable membrane where an adjacent manhole chamber will have a flow control device to restrict discharge from the site to 5.4 l/sec

6.4. Pre-development Runoff Rates

In accordance with the Modified Rational Method, the peak existing run-off from the site is calculated from the formula:

$$Q = 3.61 \times C_v \times i \times A$$

where C_v is the volumetric runoff coefficient, A is the catchment area in hectares and i is the peak rainfall intensity in mm/hr.

For the peak 1 in 1 year return period storm event this gives an existing discharge rate from the site of: $Q_1 = 3.61 \times 1.0 \times 0.3765 \times 21.82 = 29.65$ l/sec

and for the peak 1 in 30 year return period storm event this gives an existing discharge rate from the site of: $Q_{30} = 3.61 \times 1.0 \times 0.3765 \times 59.28 = 80.6$ l/sec

and for the peak 1 in 100 year return period storm event this gives an existing discharge rate from the site of: $Q_{100} = 3.61 \times 1.0 \times 0.3765 \times 81.47 = 110.7$ l/sec

6.5. Proposed Limiting Discharge Rate

Proposals are to restrict discharge rates to the Q_{Bar} 1 in 2 year PDL Greenfield runoff rate of 5.4 l/sec in order to avoid local drainage system failure. A limiting discharge rate of 5.4 l/sec is considered as far as reasonably practicable without compromising the performance and operation of flow control devices such as a hydrobrake.

A discharge rate of 5.4 l/sec would provide betterment in terms of flood risk by reducing existing runoff rates during extreme events i.e. the 1 in 100 year event. This provides a 95% betterment on the existing 100-year pre-development runoff rate of 110.7 l/sec.

A copy of the Micro Drainage calculations sheets are included as Appendix G, SuDS Proforma as Appendix H and the preliminary site drainage layout is included as Appendix I of this report.

6.6. Attenuation Storage

In order to achieve a discharge rate of 5.4 l/sec, attenuation storage will be required. An estimated storage volume of 300 m³ will be required to accommodate the 1 in 100 year plus 40% CC storm event.

6.7. Maintenance

A SuDS Maintenance Plan in accordance with CIRIA RP992 will be prepared at a later stage if required.

7. Foul Water Drainage

7.1. Existing Foul Flows

It has been assumed that all the existing properties fronting the street drain to the public foul sewer located in High Road.

7.2. Proposed Foul Flows

The proposed peak foul flow has been assessed as 4.2 l/sec however this is based on preliminary design information and may vary slightly as the design process moves forward.

7.3. Consultation

A pre-planning enquiry will need to be submitted to Thames Water to confirm capacity within the public sewer for the proposed development. A Section 106 application will be required for permission to connect to the public sewer in due course.

8. Conclusion

This report has been prepared in accordance the upcoming emerging 'draft' London Plan which requires development proposals to utilise (SuDS) where practical, aim to achieve Greenfield run-off rates and ensure that surface water run-off is managed as close to its source as possible.

The proposed development site has an area of approximately 0.3765 ha (3,765 m²) of which 3,515 m² (93%) will be impermeable surfaces that positively drains to the proposed network.

A limiting discharge rate of 5.4 l/sec is considered as far as reasonably practicable without compromising the performance and operation of flow control devices such as a hydrobrake. In order to achieve a discharge rate of 5.4 l/sec, attenuation storage will be required. An estimated storage volume of 300 m³ will be required to accommodate the 100 year plus storm event plus a 40% allowance for climate change.

Greenfield runoff rates have calculated based on the methodology explained within the Haringey SuDS Design Requirements LLFA Technical Assessment document by multiplying by a factor of three.



The proposed drainage strategy is fully complaint with national, regional and local planning policy.

The proposed peak foul flow has been assessed as 4.2 l/sec however this is based on preliminary design information and may vary slightly as the design process moves forward.

A CCTV drainage survey of the existing drainage network is required to re-use any existing connections.

Applications for Thames Water approvals are required in due course.

Appendix A – Site Location Plan



KEY PLAN

NOTES:

DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER DRAWINGS, SPECIFICATIONS, DOCUMENTS AND CONSULTANT INFORMATION.
CAD DRAWINGS BASED ON SURVEY INFORMATION BY OTHERS; ALL DIMENSIONS TO BE SITE CHECKED.
M&E ITEMS SHOWN INDICATIVELY AND ARE SUBJECT TO FURTHER SITE INVESTIGATIONS AND END USER SPECIFICATION REQUIREMENTS.
INTERNAL FURNITURE LAYOUTS SHOWN FOR INDICATIVE PURPOSES.
LANDSCAPING/PUBLIC REALM SHOWN FOR INDICATIVE PURPOSES ONLY - REFER TO REFORM LANDSCAPE ARCHITECTS DRAWINGS FOR DETAILS.

KEY:

- APPLICATION BOUNDARY
NO. XX BUILDING EXTENT

No.		DATE	DESCRIPTION	RM	AC
P1		26/02/2020	PLANNING	RM	AC
No.		DATE	DESCRIPTION	RM	AC
				DRN	CHK
REVISION HISTORY					

Architect

F3 ARCHITECTURE + INTERIORS
A: 5 Rochester Mews - London - NW1 9JB
T: 020 7267 8332
W: f3architects.com
E: info@f3architects.com

Except for Planning purposes, figured dimensions only are to be taken from this drawing.
All dimensions are in millimetres unless otherwise stated.
All dimensions shall be checked on site prior to works commencing.
Any discrepancies shall be reported to the Architect.
© Copyright F3 Architecture + Design. All rights reserved.

Health and Safety

Project Name

**NORTHUMBERLAND TERRACE PHASE 3:
NOS. 798 TO 808 HIGH ROAD AND
LAND TO REAR
798-808 HIGH ROAD
LONDON
N17 0BX**


Drawing Title

PROPOSED ROOF PLAN

Date		Status						
26/02/2020		PLANNING						
Drawn By		Checked By	Approved By		Scale	Size	Project Reference	
RM	AC	IL	1 : 200		A1	171121		
Project	Agent	Zone	Level	Type	Role	Drawing No.		Revision
NT-1000-ZZ-RF-GA-A-		20016				P1		
© Copyright F3 Architecture + Design. All rights reserved.								

© Copyright F3 Architecture + Design. All rights reserved.

Appendix B – Existing Topographic Survey



Appendix C – Preliminary Site Layouts



KEY PLAN

NOTES:
DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER DRAWINGS, SPECIFICATIONS, DOCUMENTS AND CONSULTANT INFORMATION.
CAD DRAWINGS BASED ON SURVEY INFORMATION BY OTHERS; ALL DIMENSIONS TO BE SITE CHECKED.
MADE ITEMS SHOWN INDICATIVELY AND ARE SUBJECT TO FURTHER SITE INVESTIGATIONS AND FINAL USER SPECIFICATION REQUIREMENTS.
INTERNAL FURNITURE LAYOUTS SHOWN FOR INDICATIVE PURPOSES.
LANDSCAPING/PUBLIC REALM SHOWN FOR INDICATIVE PURPOSES ONLY - REFER TO RELEVANT DRAWINGS AND SPECIFICATIONS FOR FURTHER INFORMATION.

KEY:

APPLICATION BOUNDARY

NO. XX

BUILDING EXTENT

[illegible]

Architect


ARCHITECTURE + INTERIORS

A: 5 Rochester Mews - London - NW1 9JB
T: 020 7267 8332
W: f3architects.com
E: info@f3architects.com

Except for Planning purposes, figured dimensions only are to be taken from this drawing.
All dimensions are in millimetres unless otherwise stated.
All dimensions shall be checked on site prior to works commencing.
Any discrepancies shall be reported to the Architect.
© Copyright F3 Architecture + Design. All rights reserved.

Health and Safety

Project Name	
--------------	--

Project Name
NORTHERLAND TERRACE PHASE 3:
NOS. 798 TO 808 HIGH ROAD AND
LAND TO REAR
798-808 HIGH ROAD
LONDON
N17 0BX

Drawing Title

Drawing Title

PROPOSED FIRST FLOOR PLAN

Date	Status
------	--------

Date	Status
26/02/2020	PLANNING

20/02/2020	12:11:13				
Drawn By	Checked By	Approved By	Scale	Size	Project Reference


Drawn by	Checked by	Approved by	Scale	Size	Project Reference
DM	AC	IL	1:200	A1	171121

RM	AC	IL	T: 200	AI	17/121
----	----	----	--------	----	--------

Project	Agent	Zone	Level	Type	Role	Drawing No.	Revision

NT-1000-ZZ-L01-GA-A- 20012

© Copyright F3 Architecture + Design. All rights reserved



KEY PLAN

NOTES:

DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER DRAWINGS, SPECIFICATIONS, DOCUMENTS AND CONSULT ANY INFORMATION.

ALL DRAWINGS BASED ON SURVEY INFORMATION BY OTHERS. ALL DIMENSIONS TO BE SITE CHECKED.

MAKE ITEMS SHOWN INDICATIVELY AND ARE SUBJECT TO FURTHER SITE INVESTIGATIONS AND END USER SPECIFICATION REQUIREMENTS.

INTERNAL FURNITURE LAYOUTS SHOWN FOR INDICATIVE PURPOSES ONLY.


LANDSCAPE/PUBLIC REALM SHOWN FOR INDICATIVE PURPOSES ONLY - REFER TO REFORM LANDSCAPE ARCHITECTS DRAWINGS FOR DETAILS.

KEY:

NO. XX APPLICATION BOUNDARY

NO. XX BUILDING EXTENT

NO.	REVISION	DATE	DESCRIPTION	NO.	NO.
01	01/01/2020	01/01/2020	01/01/2020	01	01
02	02/02/2020	02/02/2020	02/02/2020	02	02
03	03/03/2020	03/03/2020	03/03/2020	03	03
04	04/04/2020	04/04/2020	04/04/2020	04	04
05	05/05/2020	05/05/2020	05/05/2020	05	05
06	06/06/2020	06/06/2020	06/06/2020	06	06
07	07/07/2020	07/07/2020	07/07/2020	07	07
08	08/08/2020	08/08/2020	08/08/2020	08	08
09	09/09/2020	09/09/2020	09/09/2020	09	09
10	10/10/2020	10/10/2020	10/10/2020	10	10
11	11/11/2020	11/11/2020	11/11/2020	11	11
12	12/12/2020	12/12/2020	12/12/2020	12	12
13	13/01/2021	13/01/2021	13/01/2021	13	13
14	14/02/2021	14/02/2021	14/02/2021	14	14
15	15/03/2021	15/03/2021	15/03/2021	15	15
16	16/04/2021	16/04/2021	16/04/2021	16	16
17	17/05/2021	17/05/2021	17/05/2021	17	17
18	18/06/2021	18/06/2021	18/06/2021	18	18
19	19/07/2021	19/07/2021	19/07/2021	19	19
20	20/08/2021	20/08/2021	20/08/2021	20	20
21	21/09/2021	21/09/2021	21/09/2021	21	21
22	22/10/2021	22/10/2021	22/10/2021	22	22
23	23/11/2021	23/11/2021	23/11/2021	23	23
24	24/12/2021	24/12/2021	24/12/2021	24	24
25	25/01/2022	25/01/2022	25/01/2022	25	25
26	26/02/2022	26/02/2022	26/02/2022	26	26
27	27/03/2022	27/03/2022	27/03/2022	27	27
28	28/04/2022	28/04/2022	28/04/2022	28	28
29	29/05/2022	29/05/2022	29/05/2022	29	29
30	30/06/2022	30/06/2022	30/06/2022	30	30
31	31/07/2022	31/07/2022	31/07/2022	31	31
32	32/08/2022	32/08/2022	32/08/2022	32	32
33	33/09/2022	33/09/2022	33/09/2022	33	33
34	34/10/2022	34/10/2022	34/10/2022	34	34
35	35/11/2022	35/11/2022	35/11/2022	35	35
36	36/12/2022	36/12/2022	36/12/2022	36	36
37	37/01/2023	37/01/2023	37/01/2023	37	37
38	38/02/2023	38/02/2023	38/02/2023	38	38
39	39/03/2023	39/03/2023	39/03/2023	39	39
40	40/04/2023	40/04/2023	40/04/2023	40	40
41	41/05/2023	41/05/2023	41/05/2023	41	41
42	42/06/2023	42/06/2023	42/06/2023	42	42
43	43/07/2023	43/07/2023	43/07/2023	43	43
44	44/08/2023	44/08/2023	44/08/2023	44	44
45	45/09/2023	45/09/2023	45/09/2023	45	45
46	46/10/2023	46/10/2023	46/10/2023	46	46
47	47/11/2023	47/11/2023	47/11/2023	47	47
48	48/12/2023	48/12/2023	48/12/2023	48	48
49	49/01/2024	49/01/2024	49/01/2024	49	49
50	50/02/2024	50/02/2024	50/02/2024	50	50
51	51/03/2024	51/03/2024	51/03/2024	51	51
52	52/04/2024	52/04/2024	52/04/2024	52	52
53	53/05/2024	53/05/2024	53/05/2024	53	53
54	54/06/2024	54/06/2024	54/06/2024	54	54
55	55/07/2024	55/07/2024	55/07/2024	55	55
56	56/08/2024	56/08/2024	56/08/2024	56	56
57	57/09/2024	57/09/2024	57/09/2024	57	57
58	58/10/2024	58/10/2024	58/10/2024	58	58
59	59/11/2024	59/11/2024	59/11/2024	59	59
60	60/12/2024	60/12/2024	60/12/2024	60	60
61	61/01/2025	61/01/2025	61/01/2025	61	61
62	62/02/2025	62/02/2025	62/02/2025	62	62
63	63/03/2025	63/03/2025	63/03/2025	63	63
64	64/04/2025	64/04/2025	64/04/2025	64	64
65	65/05/2025	65/05/2025	65/05/2025	65	65
66	66/06/2025	66/06/2025	66/06/2025	66	66
67	67/07/2025	67/07/2025	67/07/2025	67	67
68	68/08/2025	68/08/2025	68/08/2025	68	68
69	69/09/2025	69/09/2025	69/09/2025	69	69
70	70/10/2025	70/10/2025	70/10/2025	70	70
71	71/11/2025	71/11/2025	71/11/2025	71	71
72	72/12/2025	72/12/2025	72/12/2025	72	72
73	73/01/2026	73/01/2026	73/01/2026	73	73
74	74/02/2026	74/02/2026	74/02/2026	74	74
75	75/03/2026	75/03/2026	75/03/2026	75	75
76	76/04/2026	76/04/2026	76/04/2026	76	76
77	77/05/2026	77/05/2026	77/05/2026	77	77
78	78/06/2026	78/06/2026	78/06/2026	78	78
79	79/07/2026	79/07/2026	79/07/2026	79	79
80	80/08/2026	80/08/2026	80/08/2026	80	80
81	81/09/2026	81/09/2026	81/09/2026	81	81
82	82/10/2026	82/10/2026	82/10/2026	82	82
83	83/11/2026	83/11/2026	83/11/2026	83	83
84	84/12/2026	84/12/2026	84/12/2026	84	84
85	85/01/2027	85/01/2027	85/01/2027	85	85
86	86/02/2027	86/02/2027	86/02/2027	86	86
87	87/03/2027	87/03/2027	87/03/2027	87	87
88	88/04/2027	88/04/2027	88/04/2027	88	88
89	89/05/2027	89/05/2027	89/05/2027	89	89
90	90/06/2027	90/06/2027	90/06/2027	90	90
91	91/07/2027	91/07/2027	91/07/2027	91	91
92	92/08/2027	92/08/2027	92/08/2027	92	92
93	93/09/2027	93/09/2027	93/09/2027	93	93
94	94/10/2027	94/10/2027	94/10/2027	94	94
95	95/11/2027	95/11/2027	95/11/2027	95	95
96	96/12/2027	96/12/2027	96/12/2027	96	96
97	97/01/2028	97/01/2028	97/01/2028	97	97
98	98/02/2028	98/02/2028	98/02/2028	98	98
99	99/03/2028	99/03/2028	99/03/2028	99	99
100	100/04/2028	100/04/2028	100/04/2028	100	100
101	101/05/2028	101/05/2028	101/05/2028	101	101
102	102/06/2028	102/06/2028	102/06/2028	102	102
103	103/07/2028	103/07/2028	103/07/2028	103	103
104	104/08/2028	104/08/2028	104/08/2028	104	104
105	105/09/2028	105/09/2028	105/09/2028	105	105
106	106/10/2028	106/10/2028	106/10/2028	106	106
107	107/11/2028	107/11/2028	107/11/2028	107	107
108	108/12/2028	108/12/2028	108/12/2028	108	108
109	109/01/2029	109/01/2029	109/01/2029	109	109
110	110/02/2029	110/02/2029	110/02/2029	110	110
111	111/03/2029	111/03/2029	111/03/2029	111	111
112	112/04/2029	112/04/2029	112/04/2029	112	112
113	113/05/2029	113/05/2029	113/05/2029	113	113
114	114/06/2029	114/06/2029	114/06/2029	114	114
115	115/07/2029	115/07/2029	115/07/2029	115	115
116	116/08/2029	116/08/2029	116/08/2029	116	116
117	117/09/2029	117/09/2029	117/09/2029	117	117
118	118/10/2029	118/10/2029	118/10/2029	118	118
119	119/11/2029	119/11/2029	119/11/2029	119	119
120	120/12/2029	120/12/2029	120/12/2029	120	120
121	121/01/2030	121/01/2030	121/01/2030	121	121
122	122/02/2030	122/02/2030	122/02/2030	122	122
123	123/03/2030	123/03/2030	123/03/2030	123	123
124	124/04/2030	124/04/2030	124/04/2030	124	124
125	125/05/2030	125/05/2030	125/05/2030	125	125
126	126/06/2030	126/06/2030	126/06/2030	126	126
127	127/07/2030	127/07/2030	127/07/2030	127	127
128	128/08/2030	128/08/2030	128/08/2030	128	128
129	129/09/2030	129/09/2030	129/09/2030	129	129
130	130/10/2030	130/10/2030	130/10/2030	130	130
131	131/11/2030	131/11/2030	131/11/2030	131	131
132	132/12/2030	132/12/2030	132/12/2030	132	132
133	133/01/2031	133/01/2031	133/01/2031	133	133
134	134/02/2031	134/02/2031	134/02/2031	134	134
135	135/03/2031	135/03/2031	135/03/2031	135	135
136	136/04/2031	136/04/2031	136/04/2031	136	136
137	137/05/2031	137/05/2031	137/05/2031	137	137
138	138/06/2031	138/06/2031	138/06/2031	138	138
139	139/07/2031	139/07/2031	139/07/2031	139	139
140	140/08/2031	140/08/2031	140/08/2031	140	140
141	141/09/2031	141/09/2031	141/09/2031	141	141
142	142/10/2031	142/10/2031	142/10/2031	142	142
143	143/11/2031	143/11/2031	143/11/2031	143	143
144	144/12/2031	144/12/2031	144/12/2031	144	144
145	145/01/2032	145/01/2032	145/01/2032	145	145
146	146/02/2032	146/02/2032	146/02/2032	146	146
147	147/03/2032	147/03/2032	147/03/2032	147	147
148	148/04/2032	148/04/2032	148/04/2032	148	148
149	149/05/2032	149/05/2032	149/05/2032	149	149
150	150/06/2032	150/06/2032	150/06/2032	150	150
151	151/07/2032	151/07/2032	151/07/2032	151	151
152	152/08/2032	152/08/2032	152/08/2032	152	152
153	153/09/2032	153/09/2032	153/09/2032	153	153
154	154/10/2032	154/10/2032	154/10/2032	154	154
155	155/11/2032	155/11/2032	155/11/2032	155	155
156	156/12/2032	156/12/2032	156/12/2032	156	156
157	157/01/2033	157/01/2033	157/01/2033	157	157
158	158/02/2033	158/02/2033	158/02/2033	158	158
159	159/03/2033	159/03/2033	159/03/2033	159	159
160	160/04/2033	160/04/2033	160/04/2033	160	160
161	161/05/2033	161/05/2033	161/05/2033	161	161
162	162/06/2033	162/06/2033	162/06/2033	162	162
163	163/07/2033	163/07/2033	163/07/2033	163	163
164	164/08/2033	164/08/2033	164/08/2033	164	164



APPLICATION BOUNDARY

BUILDING EXTENT

[illegible]

f3 ARCHITECTURE + INTERIORS
A: 5 Rochester Mews - London - NW1 9JB
T: 020 7267 8332
W: f3architects.com
E: info@f3architects.com

Except for Planning purposes, figured dimensions only are to be taken from this drawing.
All dimensions are in millimetres unless otherwise stated.
All dimensions shall be checked on site prior to works commencing.
Any discrepancies shall be reported to the Architect.
© Copyright F3 Architecture + Design. All rights reserved.


Health and Safety



Project Name
NORTHUMBERLAND TERRACE PHASE 3: NOS. 798 TO 808 HIGH ROAD AND LAND TO REAR 798-808 HIGH ROAD LONDON N17 0BX

Drawing Title
PROPOSED THIRD FLOOR PLAN

Date		Status						
26/02/2020		PLANNING						
Drawn By		Checked By		Approved By		Scale	Size	Project Reference
RM	AC	IL		1 : 200		A1	171121	
Project	Agent	Zone	Level	Type	Role	Drawing No.		Revision
NT-1000-ZZ-L03-GA-A- 20014								P1

© Copyright F3 Architecture + Design. All rights reserved





KEY PLAN

NOTES:
DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER DRAWINGS, SPECIFICATIONS, DOCUMENTS AND CONSULTANT INFORMATION.
CAD DRAWINGS BASED ON SURVEY INFORMATION BY OTHERS. ALL DIMENSIONS TO BE SITE CHECKED.
MAKE ITEMS SHOWN INDICATIVELY AND ARE SUBJECT TO FURTHER SITE INVESTIGATIONS AND END USER SPECIFICATION REQUIREMENTS.
INTERNAL FURNITURE LAYOUTS SHOWN FOR INDICATIVE PURPOSES.
LANDSCAPE/PUBLIC REALM SHOWN FOR INDICATIVE PURPOSES ONLY - REFER TO REFORM LANDSCAPE ARCHITECTS DRAWINGS FOR DETAILS.

KEY:

NO. XX APPLICATION BOUNDARY
BUILDING EXTENT

NO.	REVISION	DATE	DESCRIPTION	NO.	NO.
1				1	1
2				2	2
3				3	3
4				4	4
5				5	5
6				6	6
7				7	7
8				8	8
9				9	9
10				10	10
11				11	11
12				12	12
13				13	13
14				14	14
15				15	15
16				16	16
17				17	17
18				18	18
19				19	19
20				20	20

ARCHITECTURE + INTERIORS

A: 5 Rochester Mews - London - NW1 9JB
T: 020 7261 8532
W: f3architects.com
E: info@f3architects.com

Except for planning purposes, figured dimensions only are to be taken from this drawing.
All dimensions are in millimetres unless otherwise stated.
All dimensions shall be checked on site prior to works commencing.
Any discrepancies shall be reported to the Architect.
© Copyright F3 Architecture + Design. All rights reserved.

Health and Safety

Project Name
**NORTHUMBERLAND TERRACE PHASE 3:
NOS. 798 TO 808 HIGH ROAD AND
LAND TO REAR
798-808 HIGH ROAD
LONDON
N17 0BX**

Drawing Title PROPOSED FOURTH FLOOR PLAN					
Date 26/02/2020	Status PLANNING				
Drawn By RM	Checked By AC	Approved By IL	Scale 1:200	Size A1	Project Reference 171121
Project Agent NT-1000-ZZ-L04-GA-A-	Zone/Level 20015	Type/Role P1			



Appendix D – Thames Water Asset Map



(c) Crown Copyright and database rights 2012 Ordnance Survey 100019345

Date: 18/06/15

Scale: 1:2098

Map Centre: 533983,191315

Data updated: 26/03/15

Wastewater Plan A3

Based on the Ordnance Survey Map with the sanction of the Controller of H.M. Stationary Office License Number:- 100019345. This map is to be used for the purposes of viewing the location of Thames Water plant only. Any other uses of the map data or further copies are not permitted. The position of the apparatus shown on this plan is given without obligation and warranty, and the accuracy cannot be guaranteed. This information is valid for the date printed. Service pipes are not shown but their presence should be anticipated. No liability of any kind whatsoever is accepted by Thames Water for any error or omission. The actual position of mains and services must be verified on site before any works are undertaken.

Foul Sewer		Foul Manhole	
Surface Sewer		Surface Manhole	
Combined Sewer		Combined Manhole	
Abandoned Sewer		Abandoned Manhole	
Pressure Main		Other Manhole	
Private Asset (Colour denotes effluent type)		End Item	
Proposed Asset (Colour denotes effluent type)		S104 Boundary	

emma.bousted@urs.com



Appendix E – Ground Investigation

The Geotechnics report contained the results of a single groundwater monitoring visit on the 28th September 2009 of the vibrating wire piezometers (VWP) installed. For the vibrating wire piezometer installed in BH09/05 at a depth of 19.0mbgl (-7.0mOD) i.e. within the London Clay the recorded standing water level was 8.92mAOD.

Buro Happold stated in their report that the Thanet Sand is confined by the Lambeth Group and will be under sub-artesian pressure. They also commented that the London Clay was in hydraulic continuity with the Kempton Park Gravels and where groundwater entries were encountered within the London Clay they coincided with layers or lenses of granular materials or claystone horizons. Furthermore they also concluded that the London Clay was under drained by the Lambeth Group.

On the basis of the above results and observations, groundwater entries should be allowed when carrying out any excavations, pile construction within the Kempton Parks Gravels, London Clay. Lambeth Group and Thanet Sand. Furthermore, higher perched water entries should also be allowed from within the made ground and Enfield Silt materials.

C PRELIMINARY GEOTECHNICAL RECOMMENDATIONS

7 Swelling and Shrinkage

The Enfield Silt materials were typically classified as clays of low to high plasticity. The number of reported tests was limited and, subject to further confirmatory testing, these materials should be assumed to be of NHBC Medium Volume Change Potential.

The underlying Kempton Park Gravels will have negligible swelling and shrinkage Potential.

The underlying London Clay materials have a classification of NHBC High Volume Change Potential. However given the presence of the overlying non-shrinkable Kempton Park Gravels, and the depth of these materials, no specific precautions in relation to swelling and shrinkage of the London Clay materials is anticipated.

8 Soakaways

Subject to confirmatory testing, and on the basis of the particle size distributions carried out on the Kempton Park Gravels, they are expected to have good soakage properties. Drainage of the site to soakaways installed within the Kempton Park Gravels could be considered. However storage would be reduced due to the groundwater table. Furthermore, noting that the depth of the made ground and Enfield Silt materials was sometimes in the region of 3.1-3.3mbgl, the surface of the gravels could be deep, making the installation of soakaway chambers into these materials impractical.

Discharge of soakaways into made ground should be avoided as inundation of made ground would lead to collapse settlements of these materials. In addition, ground contamination would need to be considered as discharge of water in contaminated ground is not permitted by the Environment Agency.

Appendix F – Greenfield Runoff Rates

Greenfield runoff rate estimation for sites

www.uksuds.com | Greenfield runoff tool

Calculated by:

Niall Greenan

Site name:

Northumberland Terrace

Site location:

Northumberland Rd, Tottenham, London

This is an estimation of the greenfield runoff rates that are used to meet normal best practice criteria in line with Environment Agency guidance “Rainfall runoff management for developments”, SC030219 (2013) , the SuDS Manual C753 (Ciria, 2015) and the non-statutory standards for SuDS (Defra, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Site Details

Latitude:

51.60593° N

Longitude:

0.06752° W

Reference:

523804789

Date:

Feb 20 2020 16:48

Runoff estimation approach

FEH Statistical

Notes

Site characteristics

Total site area (ha):

0.3765

Methodology

Q_{MED} estimation method:

Specify QMed manually

Q_{MED} (l/s):

1.6

Q_{BAR} / Q_{MED} factor:

1.14

Hydrological characteristics

	Default	Edited
SAAR (mm):	625	625
Hydrological region:	6	6
Growth curve factor 1 year:	0.85	0.85
Growth curve factor 30 years:	2.3	2.3
Growth curve factor 100 years:	3.19	3.19
Growth curve factor 200 years:	3.74	3.74

(1) Is Q_{BAR} < 2.0 l/s/ha?

When Q_{BAR} is < 2.0 l/s/ha then limiting discharge rates are set at 2.0 l/s/ha.

(2) Are flow rates < 5.0 l/s?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

(3) Is SPR/SPRHOST ≤ 0.3?

Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.

Greenfield runoff rates

	Default	Edited
Q _{BAR} (l/s):		1.82
1 in 1 year (l/s):		1.54
1 in 30 years (l/s):		4.18
1 in 100 year (l/s):		5.8
1 in 200 years (l/s):		6.8

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at www.uksuds.com. The use of this tool is subject to the UK SuDS terms and conditions and licence agreement , which can both be found at www.uksuds.com/terms-and-conditions.htm. The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.

Appendix G – Micro Drainage Calculation Sheets

Lyons O'Neill		Page 1
5 Maidstone Mews	Northern Studios	
72-76 Borough High Street	Attenuation Estimate	
London SE1 1GN	100 year + 40% CC	
Date 24/02/2020 09:17	Designed by N.G.	
File ATTENUATION ESTIMATE.SRCX	Checked by N.G.	
XP Solutions	Source Control 2018.1	

Summary of Results for 100 year Return Period (+40%)

Half Drain Time : 474 minutes.

Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control Σ (l/s)	Max Outflow (l/s)	Max Volume (m ³)	Status
15 min Summer	11.108	0.408	0.0	5.4	5.4	135.6	0 K
30 min Summer	11.220	0.520	0.0	5.4	5.4	173.0	0 K
60 min Summer	11.323	0.623	0.0	5.4	5.4	207.0	0 K
120 min Summer	11.470	0.770	0.0	5.4	5.4	255.9	0 K
180 min Summer	11.542	0.842	0.0	5.5	5.5	279.8	0 K
240 min Summer	11.577	0.877	0.0	5.6	5.6	291.7	0 K
360 min Summer	11.592	0.892	0.0	5.7	5.7	296.6	0 K
480 min Summer	11.575	0.875	0.0	5.6	5.6	290.9	0 K
600 min Summer	11.551	0.851	0.0	5.6	5.6	282.9	0 K
720 min Summer	11.524	0.824	0.0	5.5	5.5	274.0	0 K
960 min Summer	11.469	0.769	0.0	5.4	5.4	255.6	0 K
1440 min Summer	11.362	0.662	0.0	5.4	5.4	220.1	0 K
2160 min Summer	11.213	0.513	0.0	5.4	5.4	170.6	0 K
2880 min Summer	11.087	0.387	0.0	5.4	5.4	128.7	0 K
4320 min Summer	10.929	0.229	0.0	5.4	5.4	76.1	0 K
5760 min Summer	10.852	0.152	0.0	5.2	5.2	50.5	0 K
7200 min Summer	10.822	0.122	0.0	4.8	4.8	40.5	0 K
8640 min Summer	10.808	0.108	0.0	4.2	4.2	35.8	0 K
10080 min Summer	10.798	0.098	0.0	3.8	3.8	32.6	0 K
15 min Winter	11.108	0.408	0.0	5.4	5.4	135.6	0 K

Storm Event	Rain (mm/hr)	Flooded Volume (m ³)	Discharge Volume (m ³)	Time-Peak (mins)
15 min Summer	166.296	0.0	138.4	26
30 min Summer	106.866	0.0	178.2	40
60 min Summer	65.333	0.0	220.3	70
120 min Summer	42.102	0.0	284.2	128
180 min Summer	31.992	0.0	324.1	186
240 min Summer	26.056	0.0	352.0	244
360 min Summer	19.167	0.0	388.4	360
480 min Summer	15.221	0.0	411.3	420
600 min Summer	12.646	0.0	427.1	482
720 min Summer	10.828	0.0	438.8	544
960 min Summer	8.424	0.0	455.0	676
1440 min Summer	5.846	0.0	473.2	952
2160 min Summer	4.032	0.0	491.7	1352
2880 min Summer	3.101	0.0	504.0	1704
4320 min Summer	2.153	0.0	524.1	2380
5760 min Summer	1.672	0.0	544.2	3016
7200 min Summer	1.386	0.0	563.8	3680
8640 min Summer	1.196	0.0	583.4	4416
10080 min Summer	1.061	0.0	602.9	5144
15 min Winter	166.296	0.0	138.4	26

Lyons O'Neill		Page 2
5 Maidstone Mews	Northern Studios	
72-76 Borough High Street	Attenuation Estimate	
London SE1 1GN	100 year + 40% CC	
Date 24/02/2020 09:17	Designed by N.G.	
File ATTENUATION ESTIMATE.SRCX	Checked by N.G.	
XP Solutions	Source Control 2018.1	

Summary of Results for 100 year Return Period (+40%)

Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max Outflow (l/s)	Max Volume (m³)	Status
30 min Winter	11.220	0.520	0.0	5.4	5.4	173.0	0 K
60 min Winter	11.323	0.623	0.0	5.4	5.4	207.1	0 K
120 min Winter	11.471	0.771	0.0	5.4	5.4	256.4	0 K
180 min Winter	11.545	0.845	0.0	5.5	5.5	280.9	0 K
240 min Winter	11.582	0.882	0.0	5.6	5.6	293.2	0 K
360 min Winter	11.600	0.900	0.0	5.7	5.7	299.2	0 K
480 min Winter	11.581	0.881	0.0	5.6	5.6	293.0	0 K
600 min Winter	11.550	0.850	0.0	5.6	5.6	282.8	0 K
720 min Winter	11.520	0.820	0.0	5.5	5.5	272.7	0 K
960 min Winter	11.453	0.753	0.0	5.4	5.4	250.3	0 K
1440 min Winter	11.313	0.613	0.0	5.4	5.4	203.9	0 K
2160 min Winter	11.099	0.399	0.0	5.4	5.4	132.7	0 K
2880 min Winter	10.952	0.252	0.0	5.4	5.4	83.9	0 K
4320 min Winter	10.826	0.126	0.0	4.9	4.9	41.9	0 K
5760 min Winter	10.800	0.100	0.0	3.9	3.9	33.3	0 K
7200 min Winter	10.787	0.087	0.0	3.3	3.3	29.0	0 K
8640 min Winter	10.779	0.079	0.0	2.8	2.8	26.3	0 K
10080 min Winter	10.773	0.073	0.0	2.5	2.5	24.3	0 K

Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)
30 min Winter	106.866	0.0	178.2	40
60 min Winter	65.333	0.0	220.3	68
120 min Winter	42.102	0.0	284.2	124
180 min Winter	31.992	0.0	324.1	182
240 min Winter	26.056	0.0	352.0	238
360 min Winter	19.167	0.0	388.4	350
480 min Winter	15.221	0.0	411.3	454
600 min Winter	12.646	0.0	427.1	492
720 min Winter	10.828	0.0	438.8	564
960 min Winter	8.424	0.0	455.0	720
1440 min Winter	5.846	0.0	473.3	1026
2160 min Winter	4.032	0.0	491.7	1408
2880 min Winter	3.101	0.0	504.0	1732
4320 min Winter	2.153	0.0	524.2	2292
5760 min Winter	1.672	0.0	544.2	2992
7200 min Winter	1.386	0.0	563.8	3680
8640 min Winter	1.196	0.0	583.4	4408
10080 min Winter	1.061	0.0	603.0	5144

Lyons O'Neill		Page 3
5 Maidstone Mews 72-76 Borough High Street London SE1 1GN	Northern Studios Attenuation Estimate 100 year + 40% CC	
Date 24/02/2020 09:17 File ATTENUATION ESTIMATE.SRCX	Designed by N.G. Checked by N.G.	
XP Solutions Source Control 2018.1		

Rainfall Details

Rainfall Model FEH Site Location GB 533905 191448 Winter Storms Yes Shortest Storm (mins) 15
Return Period (years) 100 Data Type Point Cv (Summer) 0.900 Longest Storm (mins) 10080
FEH Rainfall Version 2013 Summer Storms Yes Cv (Winter) 0.900 Climate Change % +40

Time Area Diagram

Total Area (ha) 0.377

Time (mins) Area			Time (mins) Area			Time (mins) Area		
From:	To:	(ha)	From:	To:	(ha)	From:	To:	(ha)
0	4	0.126	4	8	0.126	8	12	0.126

Appendix H – SuDS Proforma


1. Project & Site Details	Project / Site Name (including sub-catchment / stage / phase where appropriate)	Northumberland Terrace
	Address & post code	Northumberland Park Road, Tottenham, London
	OS Grid ref. (Easting, Northing)	E 533923
		N 191438
	LPA reference (if applicable)	N/A
	Brief description of proposed work	The proposals consist of a new-build four storey building stretching across an L shape footprint.
	Total site Area	3,765 m ²
	Total existing impervious area	3,765 m ²
	Total proposed impervious area	3,515 m ²
	Is the site in a surface water flood risk catchment (ref. local Surface Water Management Plan)?	Located in CDA Group4_061
	Existing drainage connection type and location	To public surface water sewer in High Road.
	Designer Name	Niall Greenan
Designer Position	Head of Civil Engineering	
Designer Company	Lyons O'Neill	

2. Proposed Discharge Arrangements	2a. Infiltration Feasibility		
	Superficial geology classification	Kempton Park Gravel Member	
	Bedrock geology classification	London Clay Formation	
	Site infiltration rate	0	m/s
	Depth to groundwater level	3.9	m below ground level
	Is infiltration feasible?	No	
	2b. Drainage Hierarchy		
		Feasible (Y/N)	Proposed (Y/N)
	1 store rainwater for later use	Y	N
	2 use infiltration techniques, such as porous surfaces in non-clay areas	Y	Y
	3 attenuate rainwater in ponds or open water features for gradual release	N	N
	4 attenuate rainwater by storing in tanks or sealed water features for gradual release	Y	Y
	5 discharge rainwater direct to a watercourse	N	N
	6 discharge rainwater to a surface water sewer/drain	Y	Y
	7 discharge rainwater to the combined sewer.	N	N
	2c. Proposed Discharge Details		
	Proposed discharge location	Re-use existing subject to survey.	
	Has the owner/regulator of the discharge location been consulted?	No	


3. Drainage Strategy	3a. Discharge Rates & Required Storage				
		Greenfield (GF) runoff rate (l/s)	Existing discharge rate (l/s)	Required storage for GF rate (m ³)	Proposed discharge rate (l/s)
	Qbar	GF x 3 = 5.4			
	1 in 1	GF x 3 = 4.4	29.6	90	5.4
	1 in 30	GF x 3 = 12.6	59.3	161	5.4
	1 in 100	GF x 3 = 17.4	81.5	213	5.4
	1 in 100 + CC				5.4
	Climate change allowance used		40%		
	3b. Principal Method of Flow Control		Hydrobrake		
	3c. Proposed SuDS Measures				
			Catchment area (m ²)	Plan area (m ²)	Storage vol. (m ³)
	Rainwater harvesting		0		0
	Infiltration systems		0		0
	Green roofs		0	0	0
	Blue roofs		0	0	0
	Filter strips		0	0	0
	Filter drains		0	0	0
	Bioretention / tree pits		155	0	155
	Pervious pavements		0	0	0
	Swales		0	0	0
	Basins/ponds		0	0	0
	Attenuation tanks		3610		3610
	Total		3765	0	3765

4. Supporting Information	4a. Discharge & Drainage Strategy	Page/section of drainage report
	Infiltration feasibility (2a) – geotechnical factual and interpretive reports, including infiltration results	Appendix E
	Drainage hierarchy (2b)	Page 6, Section 5
	Proposed discharge details (2c) – utility plans, correspondence / approval from owner/regulator of discharge location	Appendix A to I
	Discharge rates & storage (3a) – detailed hydrologic and hydraulic calculations	Appendix G
	Proposed SuDS measures & specifications (3b)	Pa
	4b. Other Supporting Details	Page/section of drainage report
	Detailed Development Layout	Appendix A
	Detailed drainage design drawings, including exceedance flow routes	Appendix A to I
	Detailed landscaping plans	Appendix C
	Maintenance strategy	O&M Manual
	Demonstration of how the proposed SuDS measures improve:	
	a) water quality of the runoff?	N/A
	b) biodiversity?	N/A
	c) amenity?	Manages runoff

Appendix I – Preliminary Site Drainage Layout



HIGH ROAD



- ## General Notes
1. This drawing is to be read in conjunction with all relevant Architect's and engineers drawings and specifications.
 2. This drawing is only to be scaled from for the purposes of estimating and approximate sizing only. If exact dimensions are relied upon, written dimensions supersede any scaled dimension. Overall setting out is to Architect's details and this drawing therefore should be read in conjunction with their information.
 3. All waterproofing, drainage, levels and finishes by others.
 4. All temporary works by others.
 5. Fire protection to Architect's details.
 6. All dimensions are in mm unless noted otherwise.
 7. All levels are in m unless noted otherwise.
 8. All RWP's and SVP's to be confirmed by Architect.

- ### Drainage Notes
1. A CCTV drainage survey is required to assess the existing drainage network and whether existing connections can be re-used.
 2. A proposed landscape plan is required for external drainage.

P02	Issued For Planning	24/02/20	NG
P01	Issued For Planning	17/10/19	NG
Rev	Comments	Date	Chk'd

Status	Stage 2 - Concept Design
--------	--------------------------

Lyons | O'Neill
Structural Engineers

5 Maidstone Mews
72-76 Borough High Street
London
SE1 1GN

+44 (20) 7223 7222
info@lyonsoneill.co.uk
lyonsoneill.co.uk

Project

Northumberland Terrace
Phase 3

LON Project No. - 19068
Subject Preliminary Site Drainage Layout

Scale @ A1
1:200

By DB	Checked NG
----------	---------------

Drawing No.	Rev	Issue Date
19068-LON-ZZ-00-DR-C-8000	P02	24/02/20