

# Building Regulations England Part L (BREL) Compliance Report

Approved Document L1 2021 Edition, England assessed by Array SAP 10 program, Array

Date: Tue 08 Oct 2024 11:27:37

| Project Information |             |                 |                 |
|---------------------|-------------|-----------------|-----------------|
| Assessed By         | Harry Davey | Building Type   | House, Detached |
| OCDEA Registration  | EES/020345  | Assessment Date | 2024-10-08      |

| Dwelling Details |                                |                  |                    |
|------------------|--------------------------------|------------------|--------------------|
| Assessment Type  | As designed                    | Total Floor Area | 406 m <sup>2</sup> |
| Site Reference   | 7339                           | Plot Reference   | Lean               |
| Address          | 6a Grange Road, London, N6 4AP |                  |                    |

| Client Details |                         |
|----------------|-------------------------|
| Name           | Client                  |
| Company        | Company                 |
| Address        | Address, Town, AA11 1AA |

This report covers items included within the SAP calculations. It is not a complete report of regulations compliance.

| 1a Target emission rate and dwelling emission rate                       |                                         |  |    |
|--------------------------------------------------------------------------|-----------------------------------------|--|----|
| Fuel for main heating system                                             | Mains gas                               |  |    |
| Target carbon dioxide emission rate                                      | 10.08 kgCO <sub>2</sub> /m <sup>2</sup> |  |    |
| Dwelling carbon dioxide emission rate                                    | 7.58 kgCO <sub>2</sub> /m <sup>2</sup>  |  | OK |
| 1b Target primary energy rate and dwelling primary energy                |                                         |  |    |
| Target primary energy                                                    | 53.36 kWh <sub>PE</sub> /m <sup>2</sup> |  |    |
| Dwelling primary energy                                                  | 44.9 kWh <sub>PE</sub> /m <sup>2</sup>  |  | OK |
| 1c Target fabric energy efficiency and dwelling fabric energy efficiency |                                         |  |    |
| Target fabric energy efficiency                                          | 48.0 kWh/m <sup>2</sup>                 |  |    |
| Dwelling fabric energy efficiency                                        | 39.8 kWh/m <sup>2</sup>                 |  | OK |

| 2a Fabric U-values               |                                                        |                                               |                                         |     |
|----------------------------------|--------------------------------------------------------|-----------------------------------------------|-----------------------------------------|-----|
| Element                          | Maximum permitted average U-Value [W/m <sup>2</sup> K] | Dwelling average U-Value [W/m <sup>2</sup> K] | Element with highest individual U-Value |     |
| External walls                   | 0.26                                                   | 0.15                                          | Walls (1) (0.15)                        | OK  |
| Party walls                      | 0.2                                                    | N/A                                           | N/A                                     | N/A |
| Curtain walls                    | 1.6                                                    | N/A                                           | N/A                                     | N/A |
| Floors                           | 0.18                                                   | 0.1                                           | Heatloss Floor 1 (0.1)                  | OK  |
| Roofs                            | 0.16                                                   | 0.1                                           | Roof (1) (0.1)                          | OK  |
| Windows, doors, and roof windows | 1.6                                                    | 0.8                                           | Opening (0.9)                           | OK  |
| Rooflights                       | 2.2                                                    | N/A                                           | N/A                                     | N/A |

| 2b Envelope elements (better than typically expected values are flagged with a subsequent (!)) |                            |                              |
|------------------------------------------------------------------------------------------------|----------------------------|------------------------------|
| Name                                                                                           | Net area [m <sup>2</sup> ] | U-Value [W/m <sup>2</sup> K] |
| Exposed wall: Walls (1)                                                                        | 458.559                    | 0.15                         |
| Ground floor: Heatloss Floor 1, Heatloss Floor 1                                               | 125.23                     | 0.1 (!)                      |
| Ground floor: Heatloss Floor 2, Heatloss Floor 2                                               | 12.26                      | 0.1 (!)                      |
| Exposed roof: Roof (1)                                                                         | 27.37                      | 0.1 (!)                      |
| Exposed roof: Roof (2)                                                                         | 63.07                      | 0.1 (!)                      |
| Exposed roof: Roof (3)                                                                         | 50.17                      | 0.1 (!)                      |

| 2c Openings (better than typically expected values are flagged with a subsequent (!)) |                        |             |              |                              |
|---------------------------------------------------------------------------------------|------------------------|-------------|--------------|------------------------------|
| Name                                                                                  | Area [m <sup>2</sup> ] | Orientation | Frame factor | U-Value [W/m <sup>2</sup> K] |
| Opening, window                                                                       | 2.112                  | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.112                  | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.112                  | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |
| Opening, window                                                                       | 2.4                    | North East  | 0.8          | 0.8 (!)                      |

| Name              | Area [m <sup>2</sup> ] | Orientation | Frame factor | U-Value [W/m <sup>2</sup> K] |
|-------------------|------------------------|-------------|--------------|------------------------------|
| Opening, window   | 1.44                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 1.44                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 1.44                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 1.44                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.16                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.16                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.16                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.16                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.16                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 4.625                  | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 4.625                  | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 4.625                  | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 6.25                   | South West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 0.72                   | North West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 0.72                   | North West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 2.73                   | North West  | 0.8          | 0.8 (!)                      |
| Opening, window   | 6.25                   | South East  | 0.8          | 0.8 (!)                      |
| Opening, roof win | 1                      | North East  | 0.7          | 0.9 (!)                      |
| Opening, roof win | 0.75                   | North West  | 0.7          | 0.9 (!)                      |

## 2d Thermal bridging (better than typically expected values are flagged with a subsequent (!))

Building part 1 - Main Dwelling: Thermal bridging calculated from linear thermal transmittances for each junction

| Main element  | Junction detail                                                   | Source                                       | Psi value [W/mK] | Drawing / reference |
|---------------|-------------------------------------------------------------------|----------------------------------------------|------------------|---------------------|
| External wall | E2: Other lintels (including other steel lintels)                 | Calculated by person with suitable expertise | 0.05             |                     |
| External wall | E3: Sill                                                          | Calculated by person with suitable expertise | 0.05             |                     |
| External wall | E4: Jamb                                                          | Calculated by person with suitable expertise | 0.05             |                     |
| Roof          | R1: Head of roof window                                           | SAP table default                            | 0.24             |                     |
| Roof          | R2: Sill of roof window                                           | SAP table default                            | 0.24             |                     |
| Roof          | R3: Jamb of roof window                                           | SAP table default                            | 0.24             |                     |
| External wall | E22: Basement floor                                               | Calculated by person with suitable expertise | 0.07             |                     |
| External wall | E5: Ground floor (normal)                                         | Calculated by person with suitable expertise | 0.16             |                     |
| External wall | E6: Intermediate floor within a dwelling                          | Calculated by person with suitable expertise | 0 (!)            |                     |
| External wall | E24: Eaves (insulation at ceiling level - inverted)               | SAP table default                            | 0.15             |                     |
| External wall | E10: Eaves (insulation at ceiling level)                          | Calculated by person with suitable expertise | 0.06             |                     |
| External wall | E11: Eaves (insulation at rafter level)                           | Calculated by person with suitable expertise | 0.04             |                     |
| External wall | E12: Gable (insulation at ceiling level)                          | Calculated by person with suitable expertise | 0.06             |                     |
| External wall | E14: Flat roof                                                    | Calculated by person with suitable expertise | 0.08             |                     |
| External wall | E16: Corner (normal)                                              | Calculated by person with suitable expertise | 0.09             |                     |
| External wall | E17: Corner (inverted - internal area greater than external area) | Calculated by person with suitable expertise | -0.09            |                     |
| Roof          | R4: Ridge (vaulted ceiling)                                       | SAP table default                            | 0.12             |                     |
| Roof          | R6: Flat ceiling                                                  | SAP table default                            | 0.12             |                     |

## 3 Air permeability (better than typically expected values are flagged with a subsequent (!))

|                                             |                                                      |    |
|---------------------------------------------|------------------------------------------------------|----|
| Maximum permitted air permeability at 50Pa  | 8 m <sup>3</sup> /hm <sup>2</sup>                    |    |
| Dwelling air permeability at 50Pa           | 3 m <sup>3</sup> /hm <sup>2</sup> , Design value (!) | OK |
| Air permeability test certificate reference |                                                      |    |

|                                                                                                                    |                               |    |
|--------------------------------------------------------------------------------------------------------------------|-------------------------------|----|
| <b>4 Space heating</b>                                                                                             |                               |    |
| <b>Main heating system 1:</b> Boiler with radiators or underfloor heating - Mains gas                              |                               |    |
| Efficiency                                                                                                         | 89.5%                         |    |
| Emitter type                                                                                                       | Both radiators and underfloor |    |
| Flow temperature                                                                                                   | 45°C                          |    |
| System type                                                                                                        |                               |    |
| Manufacturer                                                                                                       | boiler                        |    |
| Model                                                                                                              | boiler                        |    |
| Commissioning                                                                                                      |                               |    |
| <b>Secondary heating system:</b> N/A                                                                               |                               |    |
| Fuel                                                                                                               | N/A                           |    |
| Efficiency                                                                                                         | N/A                           |    |
| Commissioning                                                                                                      |                               |    |
| <b>5 Hot water</b>                                                                                                 |                               |    |
| <b>Cylinder/store</b> - type: Cylinder                                                                             |                               |    |
| Capacity                                                                                                           | 350 litres                    |    |
| Declared heat loss                                                                                                 | 2.2 kWh/day                   |    |
| Primary pipework insulated                                                                                         | Yes                           |    |
| Manufacturer                                                                                                       |                               |    |
| Model                                                                                                              |                               |    |
| Commissioning                                                                                                      |                               |    |
| <b>Waste water heat recovery system 1</b> - type: Instantaneous                                                    |                               |    |
| Efficiency                                                                                                         | 43.1%                         |    |
| Manufacturer                                                                                                       | Dutch Solar Systems BV        |    |
| Model                                                                                                              | Easyfit+                      |    |
| <b>6 Controls</b>                                                                                                  |                               |    |
| <b>Main heating 1</b> - type: Time and temperature zone control by arrangement of plumbing and electrical services |                               |    |
| Function                                                                                                           |                               |    |
| Ecodesign class                                                                                                    |                               |    |
| Manufacturer                                                                                                       |                               |    |
| Model                                                                                                              |                               |    |
| <b>Water heating</b> - type: Cylinder thermostat and HW separately timed                                           |                               |    |
| Manufacturer                                                                                                       |                               |    |
| Model                                                                                                              |                               |    |
| <b>7 Lighting</b>                                                                                                  |                               |    |
| Minimum permitted light source efficacy                                                                            | 75 lm/W                       |    |
| Lowest light source efficacy                                                                                       | 80 lm/W                       | OK |
| External lights control                                                                                            | N/A                           |    |
| <b>8 Mechanical ventilation</b>                                                                                    |                               |    |
| <b>System type:</b> Balanced whole-house mechanical ventilation with heat recovery                                 |                               |    |
| Maximum permitted specific fan power                                                                               | 1.5 W/(l/s)                   |    |
| Specific fan power                                                                                                 | 0.79 W/(l/s)                  | OK |
| Minimum permitted heat recovery efficiency                                                                         | 73%                           |    |
| Heat recovery efficiency                                                                                           | 88%                           | OK |
| Manufacturer/Model                                                                                                 | MRXBOXAB-ECO3, MRXBOXAB-ECO3B |    |
| Commissioning                                                                                                      |                               |    |
| <b>9 Local generation</b>                                                                                          |                               |    |
| N/A                                                                                                                |                               |    |
| <b>10 Heat networks</b>                                                                                            |                               |    |
| N/A                                                                                                                |                               |    |
| <b>11 Supporting documentary evidence</b>                                                                          |                               |    |
| N/A                                                                                                                |                               |    |

## 12 Declarations

### a. Assessor Declaration

This declaration by the assessor is confirmation that the contents of this BREL Compliance Report are a true and accurate reflection based upon the design information submitted for this dwelling for the purpose of carrying out the "As designed" assessment, and that the supporting documentary evidence (SAP Conventions, Appendix 1 (documentary evidence) schedules the minimum documentary evidence required) has been reviewed in the course of preparing this BREL Compliance Report.

Signed:

Assessor ID:

Name:

Date:

### b. Client Declaration

N/A